

## System Warranty

Zambelli is herewith confirming for its Rainwater-Systems a


### System Warranty.

We guarantee, that our rainwater systems will not show defects in material or production, which will impede the stability or function of the system for

**15 years.**



**Fertigungs GmbH & Co. KG**  
Passauer Straße 3+5, 94481 Grafenau.  
Tel. 0 85 55 / 4 09-0, Fax 0 85 55 / 4 09-31



The warranty starts with the handout of the materials to the buyer.

The installation of the Zambelli rainwater system has to take place according to the Zambelli installation instructions and according to roofing and plumbing industry standards.

All damages to the surface or cuts made or existing during the installation will be painted by the installer with the Zambelli correction varnish or spray.

The whole systems has to be installed with matching Zambelli products only.

An eventual claim is handled by the selling Zambelli unit only and has to be made in writing.

Our personnel will be allowed to inspect the system at the given installation location.

If the claim is accepted, Zambelli will replace the defective parts free installation site.

Labour, exchange works or consequential damages in conjunction with the accepted claim are not covered by this warranty.

This warranty is valid under normal environmental conditions, excluded are maritime or industrial environments as well as chemical, electrochemical, mechanical or other physical impacts.

All matters not handled in this warranty letter are subject to the legal conditions of the sale.



EINFACH MEISTERHAFT ENTWÄSSERT

Rainclear Systems Ltd  
Unit 34A Techno Trading Estate  
Ganton Way  
SN2 8ES Swindon Wilts

Datum Grafenau, 10.07.2018  
Ansprechpartner Schmid Sabrina

Telefon +49 8555 409-64  
Fax +49 8555 409-9964  
E-Mail sabrina.schmid@zambelli.de

### Reactions of galvanized and zinc material with wood

Dear Sir or Madame,

we would like to draw your attention on some wood that cannot be used with our galvanized and zinc roof drainage range because they contain a high volume of acids.

Therefore, please see the following list showing the wood with too high volume of acid and therefore not usable combined with our roof drainage system:

Douglas fir

Oak

Chestnut

Larch

Red Cedar

Cedar

Yours sincerely

Zambelli Fertigungs GmbH & Co. KG

Sabrina Schmid  
Export Dachentwässerung



## STORAGE INSTRUCTIONS for galvanized steel

In accordance with industry best practice please note that:

**If galvanized steel products are not stored correctly, they can be affected by corrosion, also known as “white rust”.**

Suitable provisions must be made during transport or storage to reduce the risk of white rust.

All Galvanized steel products must be stored inside or under cover, in a clean and dry environment and free of any chemical interaction.

Rapid temperature changes lead to condensation and as a consequence to white rust on galvanized steel. So all stock must be kept in constant temperature over dew point.

All stocks must be kept always on wooden or metal pallets to avoid ground contact.

**It is best practice to avoid storing galvanized steel material outside. However, if this is unavoidable, the below precautions must also be taken in addition to the above steps:**

Build a simple frame around the packets or coils and cover them with a waterproof film, tarpaulin or similar cover.

Allow for space between the packets or coils and the waterproof cap so that air can circulate freely.

Stock the packets without ground contact at a slight incline so that the rain can drain of the cap.

Check the stock area regularly in order to avoid wetness of the material. Be aware of the fact that all articles (stored at bottom, top or center of a pallet) might get wet because of the condensation and this water may not be able to flow away.

Keep the period of outside stocking as short as possible especially during the summer season as the elevated temperatures speed up the white rust process.

Zambelli Fertigungs GmbH & Co. KG  
Passauer Straße 3+5  
94481 Grafenau  
GERMANY

phone +49 85 55 409 - 0  
fax +49 85 55 409 - 30  
e-mail fertigung@zambelli.de  
www zambelli.com