



Flat Glass Rooflight to suit **builders** upstand:

	Glazed unit only	Electric concealed motors hinged opening		
	To suit external curb size (mm)	To suit external curb size (mm)		
Square	S4	700x700	720x720	
	S5	800 x 800	820 x 820	
	S7	900 x 900	920 x 920	
	S8	1000 x 1000	1020 x 1020	
	S9	1100 x 1100	1120 x 1120	
	S11	1300 x 1300	1320 x 1320	
	S17	2100 x 2100	N/A	
	Rectangular	R5	700 x 1000	720 x 1020
		R6	700 x 1300	720 x 1320
R16		1000 x 1300	1020 x 1320	
R17a		1100 x 1600	1120 x 1620	
R19		1100 x 2100	1120 x 2120	
R22z		1100 x 3100	N/A	
R30a		1600 x 3100	N/A	



Flat Glass Rooflight with **Timber Sloping Upstand:**

	Size ref	To suit roof opening size (mm)
Square	S4	600 x 600
	S5	700 x 700
	S7	800 x 800
	S8	900 x 900
	S9	1000 x 1000
	S11	1200 x 1200
Rectangular	R5	600 x 900
	R6	600 x 1200
	R16	900 x 1200
	R17a	1000 x 1500
	R19	1000 x 2000

Ventilation Options:

- Fixed – no ventilation
- Electrically opening (supplied with retractive switch as standard)

Accessories:

- Standard comfort control kit (control panel, remote control and rain sensor)
- Premium comfort control kit (open/close manual switch and internal & external temperature, wireless weather station including wind & rain sensor). Remote sold separately.