



em.glaze™ skyvu

TECHNICAL DATA SHEET | 06.06.23 | V 1.0

Introducing the new em.glaze skyvu, the stylish new aluminium roof lantern, and the clear choice for fabricators and installers. em.glaze skyvu offers a perfect blend of contemporary aesthetics, leading performance, and quick and simple installation, all from a name you can trust.



Features & Benefits

- Slim sightlines – 38mm internal rafters giving you less frame and more light
- Two styles available – traditional and contemporary
- Multiple configuration options and up to 4.5m in length to suit all projects
- Fully tested for maximum weather performance
- Low u-Values of 1.3W/m²K for a warmer, more energy-efficient home
- Building regulation compliant – Part L
- Quick and simple to install – in as little as 40 minutes
- 3-5 days lead time from stock with typical standard sizes, configurations, and colours all in stock
- 6 stock sizes – single colour (white, grey, black) and dual colour (grey on white)

Performance & Accreditation

- U-Value of 1.3 W/m²k
- 38mm sightlines
- Installation in as little as 40 minutes
- Part L Compliant
- Weather tested to BS6375

Glazing


- Ambi-neutral self-cleaning glass
- Soft neutral tone with minimal tint for a natural look to the interior space
- Advanced thermal performance
- Reflects 60% of the sun's heat away from the roof space
- Reduces the sun's glare by 63%

Upstand

To suit a timber upstand, fully weathered. 150mm off finished roof and 100mm wide.

Dimensions


Stock sizes:




1.5m x 1m




2m x 1m




2m x 1.5m



2.5m x 1.5m



3m x 1.5m



3m x 2m

Multiple configurations are available up to 4.5m in length to suit all projects.

